THE GIBSON-HOMANS COMPANY 8755.2 PAGE 1 MATERIAL SAFETY DATA SHEET NA = NOT APPLICABLE ND = NOT DETERMINED HEALTH = ABBREVIATIONS: FLAMMABILITY = REACTIVITY = PERSONAL PROTECTION = + SEE SECTION VIII NE = NOT ESTABLISHED 0 SECTION I-MATERIAL IDENTIFICATION AND USE MATERIAL NAME/IDENTIFIER: 8755, 8757 - WALLPAPER & VINYL WALLCOVERING WHEAT MANUFACTURERS NAME AND ADDRESS: GIBSON-HOMANS COMPANY
1755 ENTERPRISE PARKWAY
TWINSBURG, OHIO 44087
EMERGENCY TELEPHONE NO.: (DAY) 216/425-3255 (24 HOUR) OHIO 44087 5 (24 HOUR) REVISED: EMERGENCY TELEPHONE NO.: (DAY) 210
DATE PREPARED: JANUARY 7, 1987
CHEMICAL FAMILY: MIXTURE
CHEMICAL FORMULA/MOLECULAR WT: NA 216/843-2982 APRIL 11, 1994 TRADE NAME AND SYNONYMS: NA MATERIAL USE: WALLPAPER & VINYL WHEAT PASTE ADHESIVE SECTION II-HAZARDOUS INGREDIENTS % WT ACGIH-TLV LD50/LC50 OSHA-PEL CHEMICAL NAME NA ÇĀS CAS #-CARCINOGEN: -Sara Title III, Sect. 313 reportable: -SECTION III-PHYSICAL/CHEMICAL CHARACTERISTICS BOILING POINT: NA - POWDER

VAPOR DENSITY(AIR=1): NA

SPECIFIC GRAVITY/DENSITY(G/ML): 0.8-1.2

EVAPORATION RATE(BUAC=1): NA

WOLATILE BY VOLUME: 1-5

COEFFICIENT OF WATER/OIL DISTRIBUTION: ND

ADDRESS ABANACE BUYCLE STATE VAPOR PRESSURE (MM): NA MELTING/FREEZING POINT: NA SOLUBILITY IN WATER: FORMS GEL COEFFICIENT OF WATER/OIL DISTRIBUTION: ND ODOR THRESHOLD (PPM): APPEARANCE, PHYSICAL STATE AND ODOR: WHITE TO OFF-WHITE POWDER SECTION IV-FIRE AND EXPLOSION DATA FLASH POINT: NA
AUTO IGNITION TEMPERATURE: ND
SENSITIVITY TO CHEMICAL IMPACT: ND
EXPLOSIVE POWER: ND
EXTINGUISHING MEDIA: WATER
SPECIAL FIRE FIGHTING PROCEDURES: NA
UNUSUAL FIRE AND EXPLOSION HAZARDS: DISPERSED IN AIR, MAY BE EXPLOSIVE IF IN
FLAMMABILITY: NO
UNDER WHAT CONDITIONS: NA UNDER WHAT CONDITIONS: NA SECTION V-REACTIVITY DATA

STABILITY-MATERIAL IS: STABLE
CONDITIONS TO AVOID: FLAMES
INCOMPATIBILITY(MATERIALS TO AVOID): STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: NA

## SECTION VI-HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: SKIN. INGESTION. INHALATION.
EFFECTS OF OVEREXPOSURE, CHRONIC: NONE KNOWN
EFFECTS OF OVEREXPOSURE, ACUTE: SKIN: MAY CAUSE IRRITATION OR DERMATITIS. EYE:
MAY CAUSE BURNING AND IRRITATION UPON DIRECT CONTACT. INGESTION:
SEVERE ORAL INTOXICATION WILL LEAD TO INTENSE BURNING OF THE THROAT

INHALATION: ACUTE OVEREXPOSURE IN MIST FORM MAY RESULT IN IRRITATION
OF THROAT AND LUNGS
OF THROAT AND LUNGS
EMERGENCY AND FIRST AID PROCEDURES: SKIN: WASH WITH SOAP AND WATER. EYE: F
WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN IF IRRITATION PERSISTS.
INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: UNKNOWN
CARCINGOENICITY: NO
LOSO OF PRODUCT: ND
LC50 OF PRODUCT: ND
SYNERGISTIC MATERIALS: NA
REPRODUCTIVE EFFECTS: NO
TERATOGENIC: NO MUTAGENIC: NO

SECTION VII-PREVENTIVE MEASURES, SAFE HANDLING AND USE

LEAK AND SPILL PROCEDURES: COLLECT LARGE SPILLS WITH SHOVEL OR PUMP TO OTHER LEAKPROOF CONTAINERS. SPREAD SAND OVER SPILL AREAS. CLEAN WITH DETERGENT SOLUTION. REMOVE ALL IGNITION SOURCES. ABSORB WITH ABORDENT. SWEEP OR SCOOP UP. VENTILATE.

WASTE DISPOSAL METHOD: DISPOSE BY SANITARY LANDFILL OR INCINERATION IN ACCORDANCE WITH APPROPRIATE REGULATIONS.

ACCORDANCE WITH APPROPRIATE REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: REEP CONTAINER CLOSED WHEN NOT FLAMES. KEEP FROM FREEZING. USE WITH ADEQUATE VENTILATION.

OTHER: KEEP GUT OF THE REACH OF CHILDREN!

SECTION VIII-CONTROL MEASURES/PROTECTION INFORMATION VENTILATION: USE SUFFICIENT VENTILATION TO KEEP WITHIN OSHA PEL/TLV LIMIT. RESPIRATORY PROTECTION: USE MASK WHILE SPRAYING. AVOID INHALATION. PROTECTIVE GLOVES: USE PROTECTIVE GLOVES. SEE PROTECTIVE GLOVES. OF AVOID SPLASH. OTHER PROTECTIVE EQUIPMENT: NONE KNOWN WORK/HYGENIC PRACTICES: REMOVE CONTAMINATED CLOTHING, LANDER BEFORE REUSE.

SECTION IX-REGULATORY INFORMATION REPORTABLE QUANTITY (MIN. UNDER ANY ACT): NONE
RCRA HAZARDOUS WASTE NO: (FED) NONE
PROPER SHIPPING NAME: STARCH NOI
DOT HAZARD CLASS: NOT REGULATED
IDENTIFICATION NO: NMFC CLASS 178760 SUB. 2 NMFC CLASS 55
VOLATILE ORGANIC COMPOUNDS(VOC): 10 G/L MAX.
EXPORT CLASSIFICATION: -

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE AND SUITABLE TO THEIR CIRCUMSTANCES.